

Section 1 - Identification of Chemical Product and Company

ABN: 95 004 978 063

AUSTRALIAN WAREHOUSE DISTRIBUTORS

a division of stork industrial equipment pty ltd

239 Wickham Rd, Moorabbin, Victoria, Australia 3189

Tel 61 3 9553 1977. Fax 61 3 9553 1225. Email stork.awd@bigpond.com.au

WHOLESALE AUTOMOTIVE & INDUSTRIAL SURFACE PREPARATION & FINISHING SUPPLIES

Substance:	Blend of ingredients.
Trade Name:	Farécla G4 Liquid Rubbing Compound
Product Use:	Finishing of painted and lacquered finishes.
Creation Date:	November, 2005
Revision Date:	November, 2005

Section 2 - Hazards Identification**Statement of Hazardous Nature**

This product is classified as: Not classified as hazardous according to the criteria of NOHSC Australia.

This product does not meet the criteria of the Australian Dangerous Goods (ADG) Code. However, this is a C1 Combustible Liquid and for storage meets the definition of Dangerous Goods.

Risk Phrases: Not Hazardous - No criteria found.

Safety Phrases: S25, S36. Avoid contact with eyes. Wear suitable protective clothing.

SUSDP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good under the ADG Code.

UN Number: None allocated

Emergency Overview

Physical Description & Colour: Off-white paste.

Odour: Mild hydrocarbon odour.

Major Health Hazards: no significant risk factors have been found for this product.

Potential Health Effects**Inhalation**

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term exposure: A commonly known health hazard which has been associated historically with the inhalation of silica-containing dusts is silicosis. Silicosis is a fibrotic lung disease (development of scar tissue in the lungs) which can be progressive and disabling; it can lead to death. It is the primary health risk from breathing silica and the oldest known occupational disease.

To pose a danger to the lungs, a dust particle must be respirable. A dust particle is considered respirable if it is smaller than 10 micrometers. Dust particles that are respirable are capable of being inhaled into the conducting airways and gas exchange regions of the lungs. Dust particles larger than 10 micrometers are not capable of penetrating the defence mechanisms of the lung to produce injury to the important lower regions of the lung where oxygen transfer takes place.

There are three different types of silicosis. Chronic silicosis may result from prolonged inhalation of excessive levels of respirable silica dust, and may take many years of exposure to develop. A second type, accelerated silicosis, may occur in a relatively shorter period of time from the inhalation of intense excessive levels of respirable silica dust. Acute silicosis, the third type, develops rapidly and has been reported in occupations such as sand blasting and drilling through silica-containing rock. Cases of acute silicosis and complicated cases of chronic silicosis and accelerated silicosis can be fatal.

Skin Contact:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term skin exposure.

MATERIAL SAFETY DATA SHEET

Eye Contact:

Short Term Exposure: This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. This product, while believed to be not harmful, is likely to cause headache and gastric disturbance such as nausea and vomiting if ingested in significant quantities. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

NOHSC: No significant ingredient is classified as carcinogenic by NOHSC.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Silica (crystalline) is classed 1 by IARC - carcinogenic to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Mineral spirit	64742-47-8	10-15	not set	not set
Silica (crystalline)	14808-60-7	5-10	0.1	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Skin Contact: Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

Ingestion: If product is swallowed or gets in mouth, wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as a C1 combustible product. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Preferred extinguishing media are carbon dioxide, dry chemical, foam.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: 84°C, Closed cup

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: >250°C

Flammability Class: C1

MATERIAL SAFETY DATA SHEET

Section 6 - Accidental Release Measures

Accidental release: Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Note that this product is combustible and therefore, for Storage, meets the definition of Dangerous Goods in some states. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage.

Store packages of this product in a cool place. Keep containers dry and away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Silica (crystalline)	0.1	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: rubber, PVC.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being used.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Off-white paste.
Odour:	Mild hydrocarbon odour.
Boiling Point:	Not available.
Freezing/Melting Point:	No specific data. Pasty solid at normal temperatures.
Volatiles:	No data.
Vapour Pressure:	No data.
Vapour Density:	No data.

MATERIAL SAFETY DATA SHEET

Specific Gravity:	1.4 approx
Water Solubility:	Partially soluble.
pH:	7.0 approx
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Viscosity:	Ca 20,000cps (Brookfield) at 20°C
Autoignition temp:	>250°C

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Containers should be kept dry.

Incompatibilities: No particular Incompatibilities.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water, silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

Section 11 - Toxicological Information

Local Effects:

Target Organs: none known

Classification of Hazardous Ingredients

Ingredient

Risk Phrases

No ingredient mentioned in the List of Designated Hazardous Substances is present in this product at hazardous concentrations.

Section 12 - Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

Section 13 - Disposal Considerations

Disposal: There are many pieces of legislation covering waste disposal and they differ in each state and territory, so each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. The Hierarchy of Controls seems to be common - the user should investigate: Reduce, Reuse, and Recycle and only if all else fails should disposal be considered. Note that properties of a product may change in use, so that the following suggestions may not always be appropriate. The following may help you in properly addressing this matter for this product. This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

Section 14 - Transport Information

ADG Code: This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: Mineral spirit, (a liquid hydrocarbon) is mentioned in the SUSDP.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

AICS Australian Inventory of Chemical Substances

CAS Number Chemical Abstracts Service Registry Number

MATERIAL SAFETY DATA SHEET

Issued by: Australian Warehouse Distributors

Phone: 61 3 9553 1977

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOHSC	National Occupational Health and Safety Commission
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the NOHSC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

Copyright © Kilford & Kilford Pty Ltd, November, 2005.

<http://www.kilford.com.au/> Phone (02)9251 4532

MATERIAL SAFETY DATA SHEET