

# **LORD** MATERIAL SAFETY DATA SHEET

## **FUSOR 122EZ – Part A**

**1.1 PRODUCT NAME: FUSOR 122EZ – Part A**

**1.2 COMPANY**

**LORD CHEMICAL PRODUCTS (AUSTRALIA) PTY. LTD.**

ACN 085 209 712  
21 Beverage Drive  
Tullamarine  
Victoria 3043  
Australia

Phone: 03 - 9335 6620

Fax: 03 - 9335 6570

**1.3 EMERGENCY**

**Telephone: 1800 033 111 - ANYTIME AUSTRALIA WIDE**

**1.4 RECOMMENDED USE**

Self Levelling Seam Sealer Component

**2 COMPOSITION**

<b>Hazardous Ingredients</b>	<b>CAS No</b>	<b>%(w/v)</b>	<b>Hazardous Category</b>	<b>Risk Phases</b>
Epoxy resin	Proprietary	70	Non-hazardous	-
Alkyl phenol blocked polyisocyanate	Proprietary	20	Non-hazardous	-
Resin	Proprietary	5	Non-hazardous	-

**3 HAZARDOUS IDENTIFICATION**

Classified as non hazardous according to the criteria of Worksafe Australia.

Hazard Category: none

UN Number -  
Proper Shipping Name -  
Dangerous Goods Class -  
Subsidiary Risk -  
Hazchem Code -  
Packing Group -  
IERG Number -  
Poisons Schedule 5

# LORID

## MATERIAL SAFETY DATA SHEET

### FUSOR 122EZ – Part A

#### 4 FIRST AID MEASURES

**Swallowed:** Immediately rinse mouth with water. DO NOT INDUCE vomiting. Give plenty water or milk to drink, then raw egg. Seek immediate medical assistance.

**Eye:** Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash contaminated skin. Seek immediate medical assistance.

**Skin:** Immediately wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.

**Inhalation:** Remove victim from exposure – avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until full recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Poisons Information Centres in each State capital city can provide additional assistance for scheduled poisons.

**Advice to Doctor:** Treat symptomatically. Do not give epinephrine or related drugs. Aspiration can result in pulmonary oedema. Liquid paraffin BP may slow gastric absorption. Gastric lavage should only be undertaken after endotracheal intubation.

#### 5 FIRE - FIGHTING MEASURES

Keep containers tightly closed. Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. Fire fighters to wear self contained breathing apparatus if risk of exposure to vapour or products of combustion/decomposition. During a fire, thermal decomposition or combustion may generate irritating and/or toxic gases and particulate.

**EXTINGUISHING MEDIA:** Water fog, foam, dry agent (carbon dioxide, dry chemical powder).

#### 6 ACCIDENTAL RELEASE MEASURES

Avoid inhalation of vapours. Use self-contained breathing apparatus. Clear area of all unprotected personnel. Slippery when split. Avoid accidents, clean up immediately.

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part A

### 6 ACCIDENTAL RELEASE MEASURES - continued

Use absorbent (soil, sand or other inert materials). Wear protective equipment to prevent skin and eye contamination and inhalation of vapours. Contain – prevent run off into drains and waterways. For large spills notify Emergency Services. If contamination of sewers or waterways has occurred advise local Emergency Services.

### 7 HANDLING and STORAGE

**Handling:** Avoid skin and eye contact and inhalation of vapours. Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS1715 and AS1716. Do not handle until all safety precautions have been read and understood. Keep closure tight and container upright to prevent leakage. Empty containers should not be re-used. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or reuse.

**Storage:** Store only in well-ventilated area. Store away from organic/combustible materials/oxidising agents/foodstuffs. Keep containers closed at all times – check regularly for leaks. Avoid thermal shock. Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Keep container closed when not in use.

### 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	NOTICES
Epoxy resin	NE	NE	NE	NE	-
Alkyl phenol blocked polyisocyanate	NE	NE	NE	NE	-
Resin	NE	NE	NE	NE	-

NE = Not Established.

As published by the National Occupational Health and Safety Commission (Worksafe Australia).

Exposure Standard (TWA) is the time weighted average airborne concentration over an eight-hour working day, for day working week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part A

### 8 EXPOSURE CONTROLS and PERSONAL PROTECTION - continued

STEL (Short Term Exposure Limits) – the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

**Skin Protection:** Use neoprene, nitrile or rubber gloves to prevent skin contact.

**Eye Protection:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**Other Protective Equipment:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing and other protective equipment before storage or reuse. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS1715 and AS1716.

**Hygienic Practices:** Always wash hands before smoking, eating, drinking or using the toilet. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

### 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance	Clear viscous liquid
Odour	Epoxy
Specific Gravity	1.12
Vapour Pressure (kPa)	Not determined
Vapour Density	Heavier than air
Flash Point (°C)	> 93
Flammability Limits (v/v%)	n/a – n/a
Solubility Limits	Insoluble in H <sub>2</sub> O
Boiling Range (°C)	n/a
Freeze Point (°C)	Not determined
pH	Not applicable
% Volatile by volume	0.0
% Volatile by weight	0.0

# **LORID** MATERIAL SAFETY DATA SHEET

## **FUSOR 122EZ – Part A**

### **10 STABILITY and REACTIVITY**

**Stability:** This product is stable under normal storage conditions.

**Reactivity:** Reacts with amines, acids, water, hydroxyl or active hydrogen compounds.

Hazardous decomposition products are carbon dioxide, carbon monoxide and aldehydes. (1)

### **11 HEALTH HAZARDS and TOXICOLOGICAL INFORMATION**

#### **HEALTH EFFECTS**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled are:

#### **ACUTE EFFECTS**

**Swallowed:** Swallowing can result in nausea. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

**Eye:** May be an eye irritant.

**Skin:** Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritate contact dermatitis.

**Inhalation:** Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. (1)

#### **CHRONIC EFFECTS**

May cause respiratory or skin dermatitis problems.

#### **TOXICITY EFFECTS**

No product toxicological information is available.

### **12 ECOLOGICAL INFORMATION**

No environmental impact data found for this material.

# LORD MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part A

### 13 DISPOSAL CONSIDERATIONS

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Normally suitable for disposal by approved agent.

### 14 TRANSPORT INFORMATION

**SHIPPING NAME** none  
**Packing Group** none

Mode	Regulations	Class	Packing Group	Notes
-	UN	None	None	
Sea	IMDG	None	None	
Road/Rail	ADG Code	None	None	
Air	IATA/ICAO	None	None	

Classified as Non hazardous Substance for the purpose of transport. Refer to relevant regulations for storage and transport requirements.

This material is a Scheduled Poison (S5) and must be stored, maintained and used in accordance with the relevant regulations.

### 15 REGULATORY INFORMATION

Classification and labelling according to Worksafe Australia's Code of Practice for Labelling Workplace Substances [NOHSC –2012 (1994)]

Hazard Symbol: none

S24/S25 Avoid contact with skin and eyes.

### 16 OTHER INFORMATION

Exposure Limits: Worksafe Australia has not established A Workplace Exposure Standard for Atmospheric Contaminants in the Occupational Environment.

The information contained in this Safety Data Sheets does not replace any of the user's statutory duties in respect of performing an adequate assessment of any potential workplace risk which may occur as a result of the way in which the product is used. The user must carry out such assessments as are required by other health and safety legislation.

#### Principal References:

(1) Material Safety Data Sheet – Fusor 122EZ Part A, LORD Corporation Inc. USA.



# **LORD** MATERIAL SAFETY DATA SHEET

## **FUSOR 122EZ – Part B**

**1.1 PRODUCT NAME: FUSOR 122EZ – Part B**

**1.2 COMPANY**

**LORD CHEMICAL PRODUCTS (AUSTRALIA) PTY. LTD.**

ACN 085 209 712  
21 Beverage Drive  
Tullamarine  
Victoria 3043  
Australia

Phone: 03 - 9335 6620

Fax: 03 - 9335 6570

**1.3 EMERGENCY**

**Telephone: 1800 033 111 - ANYTIME AUSTRALIA WIDE**

**1.4 RECOMMENDED USE**

Self Levelling Seam Sealer Component

**2 COMPOSITION**

<b>Hazardous Ingredients</b>	<b>CAS No</b>	<b>%(w/v)</b>	<b>Hazardous Category</b>	<b>Risk Phases</b>
Amine compound	Proprietary	10	Xi	R21/R22, R36, R43

**3 HAZARDOUS IDENTIFICATION**

Classified as hazardous according to the criteria of Worksafe Australia.

Hazard Category: Xi (IRRITANT)

UN Number -  
Proper Shipping Name -  
Dangerous Goods Class -  
Subsidiary Risk -  
Hazchem Code -  
Packing Group -  
IERG Number -  
Poisons Schedule 6

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part B

### 4 FIRST AID MEASURES

**Swallowed:** Immediately rinse mouth with water. DO NOT INDUCE vomiting. Give plenty water or milk to drink, then raw egg. Seek immediate medical assistance.

**Eye:** Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash contaminated skin. Seek immediate medical assistance.

**Skin:** Immediately wash contaminated skin with plenty of soap and water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.

**Inhalation:** Remove victim from exposure – avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until full recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Poisons Information Centres in each State capital city can provide additional assistance for scheduled poisons.

**Advice to Doctor:** Treat symptomatically. Do not give epinephrine or related drugs. Aspiration can result in pulmonary oedema. Liquid paraffin BP may slow gastric absorption. Gastric lavage should only be undertaken after endotracheal intubation.

### 5 FIRE - FIGHTING MEASURES

Keep containers tightly closed. Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. Fire fighters to wear self contained breathing apparatus if risk of exposure to vapour or products of combustion/decomposition. During a fire, thermal decomposition or combustion may generate irritating and/or toxic gases and particulate.

**EXTINGUISHING MEDIA:** Water fog, foam, dry agent (carbon dioxide, dry chemical powder).

### 6 ACCIDENTAL RELEASE MEASURES

Avoid inhalation of vapours. Use self-contained breathing apparatus. Clear area of all unprotected personnel. Slippery when split. Avoid accidents, clean up immediately.

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part B

### 6 ACCIDENTAL RELEASE MEASURES - continued

Use absorbent (soil, sand or other inert materials). Wear protective equipment to prevent skin and eye contamination and inhalation of vapours. Contain – prevent run off into drains and waterways. For large spills notify Emergency Services. If contamination of sewers or waterways has occurred advise local Emergency Services.

### 7 HANDLING and STORAGE

**Handling:** Avoid skin and eye contact and inhalation of vapours. Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS1715 and AS1716. Do not handle until all safety precautions have been read and understood. Keep closure tight and container upright to prevent leakage. Empty containers should not be re-used. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or reuse.

**Storage:** Store only in well-ventilated area. Store away from organic/combustible materials/oxidising agents/foodstuffs. Keep containers closed at all times – check regularly for leaks. Avoid thermal shock. Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Keep container closed when not in use.

### 8 EXPOSURE CONTROLS and PERSONAL PROTECTION

	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	NOTICES
Amine compound	NE	NE	NE	NE	Sk

NE = Not Established.

As published by the National Occupational Health and Safety Commission (Worksafe Australia).

Exposure Standard (TWA) is the time weighted average airborne concentration over an eight-hour working day, for day working week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

STEL (Short Term Exposure Limits) – the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part B

### 8 EXPOSURE CONTROLS and PERSONAL PROTECTION - continued

'Sk' notice: absorption through the skin may be a significant source of exposure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

**Skin Protection:** Use neoprene, nitrile or rubber gloves to prevent skin contact.

**Eye Protection:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**Other Protective Equipment:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing and other protective equipment before storage or reuse. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS1715 and AS1716.

**Hygienic Practices:** Always wash hands before smoking, eating, drinking or using the toilet. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

### 9 PHYSICAL and CHEMICAL PROPERTIES

Appearance	Blue viscous liquid
Odour	Epoxy
Specific Gravity	1.14
Vapour Pressure (kPa)	Not determined
Vapour Density	Heavier than air
Flash Point (°C)	> 93
Flammability Limits (v/v%)	n/a – n/a
Solubility Limits	Insoluble in H <sub>2</sub> O
Boiling Range (°C)	130 – 135
Freeze Point (°C)	Not determined
pH	Not applicable
% Volatile by volume	0.0
% Volatile by weight	0.0

### 10 STABILITY and REACTIVITY

**Stability:** This product is stable under normal storage conditions.

**Reactivity:** Reacts with strong oxidising agents/acid/alkalis.

# **LORD** MATERIAL SAFETY DATA SHEET

## **FUSOR 122EZ – Part B**

### **10 STABILITY and REACTIVITY - continued**

Hazardous decomposition products are carbon dioxide, carbon monoxide, and organic or inorganic nitrogen compounds including traces of hydrogen cyanide. (1)

### **11 HEALTH HAZARDS and TOXICOLOGICAL INFORMATION**

#### **HEALTH EFFECTS**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled are:

#### **ACUTE EFFECTS**

**Swallowed:** Swallowing can result in nausea. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

**Eye:** Eye contact may cause eye damage, with conjunctivitis and potential corneal injury if not promptly and adequately treated. Eye damage may include vision disturbances and irritation.

**Skin:** May be corrosive to skin; contact may cause skin burns. May cause skin sensitisation. May cause burns.

**Inhalation:** Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. Inhalation may cause temporary blurring of vision. (1)

#### **CHRONIC EFFECTS**

May cause respiratory or skin dermatitis problems.

#### **TOXICITY EFFECTS**

No product toxicological information is available.

### **12 ECOLOGICAL INFORMATION**

No environmental impact data found for this material.

### **13 DISPOSAL CONSIDERATIONS**

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Normally suitable for disposal by approved agent.

# LORID MATERIAL SAFETY DATA SHEET

## FUSOR 122EZ – Part B

### 14 TRANSPORT INFORMATION

**SHIPPING NAME** none  
**Packing Group** none

Mode	Regulations	Class	Packing Group	Notes
-	UN	None	None	
Sea	IMDG	None	None	
Road/Rail	ADG Code	None	None	
Air	IATA/ICAO	None	None	

Classified as Non hazardous Substance for the purpose of transport. Refer to relevant regulations for storage and transport requirements.

This material is a Scheduled Poison (S6) and must be stored, maintained and used in accordance with the relevant regulations.

### 15 REGULATORY INFORMATION

Classification and labelling according to Worksafe Australia's Code of Practice for Labelling Workplace Substances [NOHSC –2012 (1994)]

Hazard Symbol: Xi (IRRITANT)

R21/R22 Harmful in contact with skin and if swallowed  
R36 Irritating to eyes  
R43 May cause sensitisation by skin contact

S26 In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information centre.  
S36/S37/S39 Wear suitable protective clothing, gloves and eye / face protection

### 16 OTHER INFORMATION

Exposure Limits: Worksafe Australia has not established A Workplace Exposure Standard for Atmospheric Contaminants in the Occupational Environment.

The information contained in this Safety Data Sheet does not replace any of the user's statutory duties in respect of performing an adequate assessment of any potential workplace risk which may occur as a result of the way in which the product is used. The user must carry out such assessments as are required by other health and safety legislation.

# **LORD** MATERIAL SAFETY DATA SHEET **FUSOR 122EZ – Part B**

<b>16 OTHER INFORMATION - continued</b>
---

**Principal References:**

- (1) Material Safety Data Sheet – Fusor 122EZ – Part B, LORD Corporation Inc. USA.
- (2) ECDIN, Toxicity summary.

The customer is advised to consult the product Technical Data Sheets for further information including advice on suitable equipment.

Information used in the compilation of this product SDS obtained from investigations conducted at outside laboratories.

Lord Chemical Products (Australia) Pty. Ltd has prepared this Material Safety Data Sheet.

Issue Date **14 December 2009**

Supersedes New issue

Reason for Revision New issue.

**'FUSOR' is a registered trademark of Lord Corporation Inc. Erie PA, USA**

The information contained in this document is intended to describe the product only in terms of health, safety and environmental requirements for the purposes of its safe handling, use and disposal and is to the best of Lord's knowledge and belief correct. Lord will be pleased to give further advice and assistance, but customers must satisfy themselves (by appropriate testing if necessary) that the product is suitable for their purposes and conditions of use and that their facilities and arrangements are suitable for handling or using the product. Accordingly Lord disclaims any liability for loss, injury or damage, which may result from the use of the product, this information, or from such advice and assistance save as may be expressly agreed under its terms of sale.

This information does not comprise a technical or performance specification for the product and customers are referred to any relevant product technical information or specification issued by Lord.

Customers are also reminded that there may be uses or application for the product which are protected by Lord's or third parties patent rights and nothing herein may be construed as an authority or encouragement to use or apply the product in contravention of such rights.